

BISTAR

TP6L72M(H)-XXX 144 half-cell

435 - 445W

9BB half-cut mono perc

KEY FEATURES



9BB half-cut cell technology

New circuit design, lower internal current, lower Rs loss



Significantly lower the risk of hot spot

Special circuit design with much lower hot spot temperature



Wider application

No water-permeability and high wear-resistance, can be widely used in high-humid, windy and dusty area



IP68 junction box

High waterproof level

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems

PERFORMANCE WARRANTY









marketing.hq@talesun.com Made in China/Thailand



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance ±3%; Binning tolerance: 0~+5W)

renormance at 310 (1 ower rolerance 13%, billing tolerance, 0 1 ow)				
Maximum Power (Pmax/W)	435	440	445	
Operating Voltage (Vmpp/V)	40.3	40.5	40.7	
Operating Current (Impp/A)	10.8	10.87	10.94	
Open-Circuit Voltage (Voc/V) (Tolerance ±4%)	49	49.2	49.4	
Short-Circuit Current (Isc/A) (Tolerance ±4%)	11.33	11.4	11.47	
Module Efficiency ηm(%)	20.0	20.2	20.4	
Performance at NMOT				
Maximum Power (Pmax/W)	324	328	332	
Operating Voltage (Vmpp/V)	37.6	37.8	38.0	
Operating Current (Impp/A)	8.62	8.67	8.73	
Open-Circuit Voltage (Voc/V)	45.6	45.8	46.0	
Short-Circuit Current (Isc/A)	9.15	9.20	9.26	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 MMOT: Irradiance at 800W/m², Ambient Temperatue 20°C, Air Mass AM1.5, Wind Speed 1m/s

MECHANICAL SPECIFICATION

Cell Type	Monocrystalline
Cell Dimensions	166*166mm
Cell Arrangement	144 (6*24)
Weight	25.5kg (56.2lbs)
Module Dimensions	2094*1038*35mm (82.44*40.87*1.38inches)
Cable Length (Portrait)	(+)300mm (11.81inches) / (-)300mm (11.81inches)
Cable Length (Landscape)	(+)1200mm (47.24inches) / (-)1200mm (47.24inches)
Cable Cross Section Size	4mm² (0.006inches²)
Front Glass	3.2mm (0.13inches) AR Coating Tempered Glass
No. of Bypass Diodes	3/6
Packing Configuration	31pcs/carton, 682pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68


OPERATING CONDITIONS

Maximun System Voltage	1500V/DC(IEC)
Operating Temperature	-40°C ~ +85°C
Maximun Series Fuse	20A
Static Loading	Snow Loading: 5400Pa/ Wind Loading: 2400Pa
Conductivity at Ground	≤0.1Ω
Safety Class	II
Resistance	≥100MΩ
Connector PV-KST4-E	VO2/xy-UR(male),PV-KBT4-EVO2/xy-UR(female); T01; LJQ-3
Fire Rating (according to UL79	0) Class C

TEMPERATURE COEFFICIENT

Temperature Coefficient Pmax	-0.36%/°C
Temperature Coefficient Voc	-0.26%/°C
Temperature Coefficient Isc	+0.043%/°C
NMOT	43±2°C

I-V CURVE



TECHNICAL DRAWINGS

